

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	3,0 mm
Wear layer	EN ISO 24340	0,7 mm
Surface treatment		K-Guard+ PU coating
Guarantee¹	Light industrial Commercial Residential	20 years 20 years 30 years
Bevelled edge		Standard
Mass per unit area	EN ISO 23997	5015 g/m ²
Standards	EN 649/EN ISO 10582	Heterogeneous PVC
Classification	EN 685/EN ISO 10874 - Light industrial EN 685/EN ISO 10874 - Commercial EN 685/EN ISO 10874 - Domestic	43: Light industrial heavy 34: Commercial very heavy 23: Domestic heavy
Reaction to fire	EN 13501-1	Bfl-s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 660-2 EN ISO 10582	Group T Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0,25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0,1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0,0147 m ² K/W Suitable for underfloor heating. Max 27° C
Slip resistance²	EN 13893 DIN 51130	DS R10
Adhesive		Please refer to our recommended adhesive list
Environmental	French VOC regulation (ISO 16000) Indoor Air Comfort Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration DIBt/AgBB ISO 14001 / ISO 9001	A+ Gold certification; Compliant low emitting VOC emissions. Indoor air quality certified; Compliant low emitting VOC emissions. External third-party verified Type III EPD Pass Manufactured to quality and environment management systems standards
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms see website.

² Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained.

For more information:

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: info@designflooring.com

www.designflooring.com

06/22



EN 14041: 2004 (DOP 2017/AS/EN/02)
Notified body 0493 Floor coverings (internal)
ISO 10874 Class 23/34/43 Manufactured to ISO 10582



	Product Code	Size		Box Quantity		Slip Resistance
		mm	inches	m ²	Pieces	DIN 51130
Wood Designs	AP01	228,6 x 76,2	9" x 3"	3,345	192 Planks	R10
	AP02	228,6 x 76,2	9" x 3"	3,345	192 Planks	R10
	AP07	228,6 x 76,2	9" x 3"	3,345	192 Planks	R10
	EW03	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	RL01	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
	RL02	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
	RL12	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
Stone Designs	LM05	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10
	LM06	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10
	LM22	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10