

|                                   | Standard   | Result   |
|-----------------------------------|--|--|
| Size                              | EN ISO 24342   | See separate table   |
| Thickness                         | EN ISO 24346   | 2,5 mm   |
| Wear layer                        | EN ISO 24340   | 0,55 mm  |
| Surface treatment                 |  | K-Guard+ PU coating  |
| Guarantee <sup>1</sup>            | Light industrial<br>Commercial<br>Residential  | 15 years<br>15 years<br>30 years   |
| Bevelled edge                     |  | Micro  |
| Mass per unit area                | EN ISO 23997   | 4398 g/m <sup>2</sup>  |
| Standards                         | EN 649/EN ISO 10582  | Heterogeneous PVC  |
| Classification                    | EN 685/EN ISO 10874 - Light industrial<br>EN 685/EN ISO 10874 - Commercial<br>EN 685/EN ISO 10874 - Domestic   | 42: Light industrial general<br>33: Commercial heavy<br>23: Domestic heavy   |
| Reaction to fire                  | EN 13501-1   | B <sub>fl</sub> -s1  |
| Staining resistance               | EN ISO 26987/EN 423  | Excellent  |
| Light fastness                    | EN ISO 105-B02   | Pass (≥ 6)   |
| Abrasion resistance               | EN 660-2<br>EN ISO 10582   | Group T<br>Type 1  |
| Flexibility                       | EN ISO 24344   | Pass   |
| Dimensional stability             | EN 434/EN ISO 23999  | Pass (≤ 0,25%)   |
| Acoustic impact noise reduction   | EN ISO 717-2/EN ISO 140-8  | ΔL <sub>w</sub> = 2 dB   |
| Electrical behaviour body voltage | EN 1815  | Pass   |
| Indentation - residual            | EN 433/EN ISO 24343-1  | Pass (≤ 0,1 mm)  |
| Castor chair continuous use       | EN 425/ISO 4918  | Pass   |
| Thermal resistance                | ISO 8302   | 0,0097 m <sup>2</sup> K/W<br>Suitable for underfloor heating. Max 27°C   |
| Slip resistance <sup>2</sup>      | EN 13893<br>DIN 51130  | DS<br>R10  |
| Adhesive                          |  | Please refer to our recommended adhesive list  |
| Environmental                     | French VOC regulation (ISO 16000)<br>Indoor Air Comfort<br><br>Floorscore SCS-EC10.3-2014 v4.0<br><br>Environmental Product Declaration<br>DIBt/AgBB<br>ISO 14001 / ISO 9001 | A+<br>Gold certification;<br>Compliant low emitting VOC emissions.<br><br>Indoor air quality certified;<br>Compliant low emitting VOC emissions.<br><br>External third-party verified Type III EPD<br>Pass<br>Manufactured to quality and environment management systems standards |
| Recycling                         |  | Suitable   |
| Phthalate free                    |  | Yes  |

<sup>1</sup> Subject to terms see website.

<sup>2</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

**For more information:**

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: [info@designflooring.com](mailto:info@designflooring.com)

[www.designflooring.com](http://www.designflooring.com)

06/22



|   |
|---|
| EN 14041: 2004 (DOP 2017/OPEN/02)                     |
| Notified body 0493<br>Floor coverings (internal)      |
| ISO 10874 Class 23/30/42<br>Manufactured to ISO 10582 |



|               | Product Code  | Size           |           | Box Quantity   |           | Slip Resistance<br>DIN 51130 |
|---------------|---------------|----------------|-----------|----------------|-----------|------------------------------|
|               |               | mm             | inches    | m <sup>2</sup> | Pieces    |                              |
| Wood Designs  | WP311         | 914,4 x 152,4  | 36" x 6"  | 3,345          | 24 Planks | R10                          |
|               | WP312         | 914,4 x 152,4  | 36" x 6"  | 3,345          | 24 Planks | R10                          |
|               | WP313         | 914,4 x 152,4  | 36" x 6"  | 3,345          | 24 Planks | R10                          |
|               | WP316         | 914,4 x 152,4  | 36" x 6"  | 3,345          | 24 Planks | R10                          |
|               | WP318         | 914,4 x 152,4  | 36" x 6"  | 3,345          | 24 Planks | R10                          |
|               | WP327         | 914,4 x 152,4  | 36" x 6"  | 3,345          | 24 Planks | R10                          |
|               | WP329         | 914,4 x 152,4  | 36" x 6"  | 3,345          | 24 Planks | R10                          |
|               | WP330         | 914,4 x 152,4  | 36" x 6"  | 3,345          | 24 Planks | R10                          |
|               | WP411         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
|               | WP412         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
|               | WP413         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
|               | WP414         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
|               | WP418         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
|               | WP419         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
|               | WP420         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
|               | WP421         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
|               | WP422         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
|               | WP423         | 1219,2 x 228,6 | 48" x 9"  | 3,345          | 12 Planks | R10                          |
| REN113        | 914,4 x 101,6 | 36" x 4"       | 3,345     | 36 Planks      | R10       |                              |
| Stone Designs | SP212         | 457,2 x 609,6  | 18" x 24" | 3,345          | 12 Tiles  | R10                          |
|               | SP213         | 457,2 x 609,6  | 18" x 24" | 3,345          | 12 Tiles  | R10                          |
|               | SP214         | 457,2 x 609,6  | 18" x 24" | 3,345          | 12 Tiles  | R10                          |
|               | SP215         | 457,2 x 609,6  | 18" x 24" | 3,345          | 12 Tiles  | R10                          |
|               | SP216         | 457,2 x 609,6  | 18" x 24" | 3,345          | 12 Tiles  | R10                          |
|               | SP217         | 457,2 x 609,6  | 18" x 24" | 3,345          | 12 Tiles  | R10                          |
|               | SP218         | 457,2 x 609,6  | 18" x 24" | 3,345          | 12 Tiles  | R10                          |
|               | SP711         | 457,2 x 914,4  | 18" x 36" | 3,345          | 8 Tiles   | R10                          |
|               | SP713         | 457,2 x 914,4  | 18" x 36" | 3,345          | 8 Tiles   | R10                          |
|               | SP714         | 457,2 x 914,4  | 18" x 36" | 3,345          | 8 Tiles   | R10                          |
|               | SP716         | 457,2 x 914,4  | 18" x 36" | 3,345          | 8 Tiles   | R10                          |