

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	3,0 mm
Wear layer	EN ISO 24340	0,55 mm
Surface treatment		K-Guard+ PU coating
Guarantee ¹	Light industrial Commercial Residential	15 years 15 years 30 years
Bevelled edge		Micro
Mass per unit area	EN ISO 23997	5187 g/m ²
Standards	EN 649/EN ISO 10582	Heterogeneous PVC
Classification	EN 685/EN ISO 10874 - Light industrial EN 685/EN ISO 10874 - Commercial EN 685/EN ISO 10874 - Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
Reaction to fire	EN 13501-1	B _{fl} -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 7)
Abrasion resistance	EN 660-2 EN ISO 10582	Group T Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0,25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 4 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0,1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0,0118 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance ²	EN 13893 DIN 51130	DS R10
Adhesive	Universal Acrylic Epoxy High Temperature+ Pressure Sensitive	Yes Yes Yes Yes Yes
Environmental	French VOC regulation (ISO 16000) Indoor Air Comfort Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration DIBt/AgBB	A+ Gold certification; Compliant low emitting VOC emissions. Indoor air quality certified; Compliant low emitting VOC emissions. External third-party verified Type III EPD Pass
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms see website.

² Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained.

For more information:

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: info@designflooring.com

www.designflooring.com

08/21



EN 14041:2004 (DOP 2020-VG/EN/02)
Notified body 0493 Floor coverings (internal)
ISO 10874 Class 23/33/42 Manufactured to ISO 10582



Product Code	Size		Box Quantity		Slip Resistance
	mm	inches	m ²	Pieces	DIN 51130
VG5-7	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW52T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW53T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW70T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW80T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW81T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW82T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW83T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW84T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW85T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW86T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW87T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW89T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW93T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW94T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW99T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW100T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW102T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW107T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW110T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW111T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW112T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW113T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW115T	1219,2 x 177,8	48" x 7"	3,252	15 Planks	R10
VGW120T	1442,4 x 228,6	56" x 9"	3,252	10 Planks	R10
VGW121T	1442,4 x 228,6	56" x 9"	3,252	10 Planks	R10
VGW122T	1442,4 x 228,6	56" x 9"	3,252	10 Planks	R10
VGW126T	1442,4 x 228,6	56" x 9"	3,252	10 Planks	R10
SM-VGW120T	711,2 x 177,8	28" x 7"	3,288	26 Planks	R10
SM-VGW121T	711,2 x 177,8	28" x 7"	3,288	26 Planks	R10
SM-VGW122T	711,2 x 177,8	28" x 7"	3,288	26 Planks	R10
SM-VGW126T	711,2 x 177,8	28" x 7"	3,288	26 Planks	R10

Wood Designs